



PRIME TRADE INC.

Binh Xuyen Industrial Zone, Binh Nguyen Commune, Phu Tho Province, Vietnam

Tel: (84) 211 3888987

Website: [www.prime.vn](http://www.prime.vn)



## DECLARATION OF PERFORMANCE

No.: DoP2702-2025/PT-CZ

- Unique identification code of the product type:  
Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$ , glossy, manufacturer SKU 05.300600.03918
- Type, batch or serial number or any other element allowing identification of the product  
Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$ , glossy, manufacturer SKU 05.300600.03918
- Intended use(s)  
For internal walls
- Name or registered trade mark, and contact address of the manufacturer  
PRIME DAI VIET JSC.  
Han Lu, Vinh Phuc Ward, Phu Tho Province, Vietnam
- Name and contact address of authorized representative  
PRIME TRADE INC.  
Binh Xuyen Industrial Zone, Binh Nguyen Commune, Phu Tho Province, Vietnam
- System(s) of assessment and verification of constancy of performance (AVCP)  
N/A
- Name and identification number of notified laboratory, if relevant  
Task(s) carried out: N/A  
AVCP system: N/A  
Document issued and date of issued: N/A
- Declared performance/s

| Characteristics                                                                                                                                                                   | Performance | Harmonised Technical Specification |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|------------------------------------|
| Reaction to fire                                                                                                                                                                  | NPD         | EN 14411:2016                      |
| Release of dangerous substance, for:                                                                                                                                              |             |                                    |
| - Cadmium*                                                                                                                                                                        | NPD         |                                    |
| - Lead*                                                                                                                                                                           | NPD         |                                    |
| Breaking strength Thickness 8.5mm $\pm$ 0.5mm                                                                                                                                     | >600N       |                                    |
| Slipperiness**                                                                                                                                                                    | NPD         |                                    |
| Bond strength/Adhesion, for:<br>Cementitious adhesive, type C2                                                                                                                    | NPD         |                                    |
| Thermal shock resistance                                                                                                                                                          | Pass        |                                    |
| Durability for:                                                                                                                                                                   |             |                                    |
| - Internal use:                                                                                                                                                                   | Pass        |                                    |
| - External use: Freeze-thaw resistance                                                                                                                                            | NPD         |                                    |
| *Only necessary in the case of materials that meet foodstuffs or when required by corresponding national statutory regulations.                                                   |             |                                    |
| **Only necessary when required by corresponding national statutory regulations; for product-specific data see technical information in our catalogue and technical specification. |             |                                    |

- The performance of the product identified in point 1 is in conformity with the declared performances in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer or authorized representative identified in point 4 and point 5.

### Sign for and on behalf of the manufacturer:

Phu Tho Province, Vietnam

Prime Dai Viet JSC.

Phung Thi Phuong Lai  
Head of QC Department

Prime Trade Inc.

Nguyen Thuy Tam  
Export Sales Manager